

Tag Number	Manufacturer	Unit Model	Unit Size	Max Operating Weight (lb)	Length X Width (feet)	Actual Airflow (CFM)	Outdoor Airflow (CFM)
RTU-14	Trane	ZC072F4RY	6 Tons	1188	7.39 x 4.44	2250	225

Notes:

1. Option to All Units: R410A refrigerant, Hinged panels for 2" MERV 8 Filters, Microprocessor controls, Circuit Breaker D BACnet Communications, Clogged Filter Switch & Condenser Drain Pan Overflow Switch, Stainless Steel Drain Pan, Room

Power Exhaust	Supply Fan Drive Type	External Static Pressure (in Wg)	Cooling Entering Air DB (F)	Cooling Entering Air WB (F)	Cooling Evap LAT DB (F)	Cooling Evap LAT WB (F)	Cooling LAT DB (F)
No	VSB	1.3	80	67	56.81	56.71	58.69

Compr. Power Input (kW)	Fan RPM	Motor Power (BHP)	Volts- Phase- Hertz	MCA	MOP (AMP)	EER	150.00
4.26	1177	1.15	480-3-60	22	30	12.6	23.20

Power Exhaust	Supply Fan Drive Type	External Static Pressure (in Wg)	Cooling Entering Air DB (F)	Cooling Entering Air WB (F)	Cooling Evap LAT DB (F)	Cooling Evap LAT WB (F)	Cooling LAT DB (F)
No	VSB	1.3	80	67	56.81	56.71	58.69

disconnect, Low Leak economizer with barometric relief, eFlex Compressor, PVC drain trap, Target OEM Controller, GFCI
 n Sensor with Temperature Adjustment with Override, Standard Condenser with Hail Guard, Gas Regulator

Cooling LAT WB
(F)

57.45

Notes

See Note 1

Cooling LAT WB (F)	Gross Cooling Capacity (Total MBH)	Gross Sensible Cooling Capacity (MBH)	Gas Htg Entering Air Temp (F)	Gas Heating Leaving Air Temp (F)	Heating Capacity (L-M-H)	Gas Hgt Capacity Input (MBH)	Gas Heating Capacity Output (MBH)
57.45	70.31	55.31	70	109.8	Medium	120	97.2

Receptacle- field wired, Hold down Clips,

Compr. Power Input (kW)	Fan RPM	Motor Power (BHP)	Volts- Phase- Hertz	MCA	MOP (AMP)	EER	150.00
4.26	1177	1.15	480-3-60	22	30	12.6	23.20

Notes

See Note 1