

Tag Number	Manufacturer	Unit Model	Unit Size	Max Operating Weight (lb)	Length X Width (feet)
RTU-37	Trane	YZD210F4RXC	17.5 Tons	2723	10.14 x 7.02

Tag Number	Gross Cooling Capacity (Total MBH)	Gross Sensible Cooling Capacity (MBH)	Gas Htg Entering Air Temp (F)	Gas Heating Leaving Air Temp (F)	Heating Capacity (L-M-H)
RTU-37	205.38	169.16	70	96.33	Low

<b>Tag Number</b>	<b>Manufacturer</b>	<b>Unit Model</b>	<b>Unit Size</b>	<b>Max Operating Weight (lb)</b>	<b>Length X Width (feet)</b>
RTU-37	Trane	YZD210F4RXC	17.5 Tons	2723	10.14 x 7.02

Notes:

1. Option to All Units: R410A refrigerant, Hinged panels for 2" MERV 8 Filters, Microprocessor controls, Circuit BACnet Communications, Clogged Filter Switch & Condenser Drain Pan Overflow Switch, Stainless Steel Drain

<b>Actual Airflow (CFM)</b>	<b>Outdoor Airflow (CFM)</b>	<b>Power Exhaust</b>	<b>Supply Fan Drive Type</b>	<b>External Static Pressure (in Wg)</b>	<b>Cooling Entering Air DB (F)</b>
7000	700	Yes	VSB	1.43	80

<b>Gas Hgt Capacity Input (MBH)</b>	<b>Gas Heating Capacity Output (MBH)</b>	<b>Compr. Power Input (kW)</b>	<b>Fan RPM</b>	<b>Motor Power (BHP)</b>	<b>Volts- Phase- Hertz</b>
200	200	12.56	911	5.48	480-3-60

<b>Actual Airflow (CFM)</b>	<b>Outdoor Airflow (CFM)</b>	<b>Power Exhaust</b>	<b>Supply Fan Drive Type</b>	<b>External Static Pressure (in Wg)</b>	<b>Cooling Entering Air DB (F)</b>
7000	700	Yes	VSB	1.43	80

Breaker Disconnect, Low Leak economizer with barometric relief, eFlex Compressor, PVC drain trap, Target OE Pan, Room Sensor with Temperature Adjustment with Override, Standard Condenser with Hail Guard, Gas Reg

Cooling Entering Air WB (F)	Cooling Evap LAT DB (F)	Cooling Evap LAT WB (F)	Cooling LAT DB (F)	Cooling LAT WB (F)
67	57.62	57.56	60.23	58.56

MCA	MOP (AMP)	EER	150.00	Notes
45	50	12.2	18.90	See Note 1

<b>Cooling Entering Air WB (F)</b>	<b>Cooling Evap LAT DB (F)</b>	<b>Cooling Evap LAT WB (F)</b>	<b>Cooling LAT DB (F)</b>	<b>Cooling LAT WB (F)</b>	<b>Gross Cooling Capacity (Total MBH)</b>
67	57.62	57.56	60.23	58.56	205.38

M Controller, GFCI Receptacle- field wired, Hold down Clips,  
ulator

---



<b>Gross Sensible Cooling Capacity (MBH)</b>	<b>Gas Htg Entering Air Temp (F)</b>	<b>Gas Heating Leaving Air Temp (F)</b>	<b>Heating Capacity (L- M-H)</b>	<b>Gas Hgt Capacity Input (MBH)</b>	<b>Gas Heating Capacity Output (MBH)</b>
169.16	70	96.33	Low	200	200

---





<b>Compr. Power Input (kW)</b>	<b>Fan RPM</b>	<b>Motor Power (BHP)</b>	<b>Volts- Phase- Hertz</b>	<b>MCA</b>	<b>MOP (AMP)</b>
12.56	911	5.48	480-3-60	45	50

---



<b>EER</b>	<b>150.00</b>	<b>Notes</b>
12.2	18.90	See Note 1