

Tag Number	Manufacturer	Unit Model	Unit Size	Max Operating Weight (lb)	Length X Width (feet)	Actual Airflow (CFM)	Outdoor Airflow (CFM)
RTU-51	Trane	YZD150F4RXC	12.5 Tons	2550	10.14 x 7.02	4600	460
Tag Number	Gross Cooling Capacity (Total MBH)	Gross Sensible Cooling Capacity (MBH)	Gas Htg Entering Air Temp (F)	Gas Heating Leaving Air Temp (F)	Heating Capacity (L-M-H)	Gas Hgt Capacity Input (MBH)	Gas Heating Capacity Output (MBH)
RTU-51	151.98	116.15	70	94	Low	120	120

Tag Number	Manufacturer	Unit Model	Unit Size	Max Operating Weight (lb)	Length X Width (feet)	Actual Airflow (CFM)	Outdoor Airflow (CFM)
RTU-51	Trane	ZD150F4RX	12.5 Tons	2550	10.14 x 7.02	4600	460

Notes:

- Option to All Units: R410A refrigerant, Hinged panels for 2" MERV 8 Filters, Microprocessor controls, Circuit Breaker I BACnet Communications, Clogged Filter Switch & Condenser Drain Pan Overflow Switch, Stainless Steel Drain Pan, Roo
- Rooftop unit to have dehumidification control, provide humidistat as shown on plan and connect to integral rooftop

Power Exhaust	Supply Fan Drive Type	External Static Pressure (in Wg)	Cooling Entering Air DB (F)	Cooling Entering Air WB (F)	Cooling Evap LAT DB (F)	Cooling Evap LAT WB (F)	Cooling LAT DB (F)
Yes	VSB	1.2	80	67	56.62	56.24	58.64

Compr. Power Input (kW)	Fan RPM	Motor Power (BHP)	Volts- Phase- Hertz	MCA	MOP (AMP)	EER	150.00
10.12	745	2.53	480-3-60	36	45	12.4	19.60



Power Exhaust	Supply Fan Drive Type	External Static Pressure (in Wg)	Cooling Entering Air DB (F)	Cooling Entering Air WB (F)	Cooling Evap LAT DB (F)	Cooling Evap LAT WB (F)	Cooling LAT DB (F)
Yes	VSB	1.2	80	67	56.62	56.24	58.64

Disconnect, Low Leak economizer with barometric relief, eFlex Compressor, PVC drain trap, Target OEM Controller, GFC m Sensor with Temperature Adjustment with Override, Standard Condenser with Hail Guard, Gas Regulator unit to enable dehumidification control sequence

Cooling LAT WB (F)
57.03
Notes
See Note 1,2

Cooling LAT WB (F)	Gross Cooling Capacity (Total MBH)	Gross Sensible Cooling Capacity (MBH)	Gas Htg Entering Air Temp (F)	Gas Heating Leaving Air Temp (F)	Heating Capacity (L-M-H)	Gas Hgt Capacity Input (MBH)	Gas Heating Capacity Output (MBH)
57.03	151.98	116.15	70	94	Low	120	120

⌋ Receptacle- field wired, Hold down Clips,

Compr. Power Input (kW)	Fan RPM	Motor Power (BHP)	Volts- Phase- Hertz	MCA	MOP (AMP)	EER	150.00
10.12	745	2.53	480-3-60	36	45	12.4	19.60

Notes

See Note
1,2